

NEW FEATURES - RELEASE 3.7

- ▶ Improved CT Saturation Stabilization
- ▶ Improved design of the PC tools
- ▶ Configurable SCADA protocols:
- ▶ Modbus, Profibus, IEC 60870-5-103/-104, DNP3

All HighPROTEC devices have been type tested and certified by KEMA Laboratories (IEC 60255-1:2009).



APPLICATION

The various protective functions of the MRDT4 are specifically tailored to the protection of two winding transformers. The device offers in addition to the differential protection various communication and backup protection functions.

Furthermore the MRDT4 can also be used as a cost-optimized generator differential protection device, where it is even possible to have a step-up transformer integrated into the protection zone.

The protection functions of the MRDT4 have been adapted to comply with the requirements of the VDE-AR-N-4110:2018.

ALL INCLUSIVE:

- ▶ All protection features without extra charge
- ▶ Parameter setting and evaluation software
- ▶ Disturbance record analysis software

TRANSFORMER PHASE DIFFERENTIAL PROTECTION

- ▶ Stabilized phase differential protection with transients and C.T. saturation detection
- ▶ Various selectable transformer groups
- ▶ Zero sequence removal
- ▶ Three point slope characteristic
- ▶ High set element (non-restraint)

TWO ELEMENTS GROUND DIFFERENTIAL PROTECTION

- ▶ Three point slope characteristic
- ▶ High set element (non-restraint)
- ▶ Wattmetric Ground Fault Protection

BACKUP PROTECTION

- ▶ 4 Elements Overcurrent/short-circuit protection (non-directional)
- ▶ 4 Elements Earth fault protection (non-directional)
- ▶ Tripping characteristics: DEFT
ANSI: NINV, VINV, EINV,
IEC: NINV, VINV, LINV, EINV, RXiDG
Thermal Flat, IT, I2T, I4T
- ▶ Two Elements Unbalanced Load Protection

LOGIC

- ▶ Up to 80 logic equations for protection, control and monitoring

COMPREHENSIVE MEASURED VALUES AND STATISTICS

- ▶ THD (total harmonic distortion)
- ▶ Current phasors and angles
- ▶ RMS and fundamental
- ▶ Sequence currents
- ▶ Differential currents

TEMPERATURE PROTECTION

- ▶ Thermal replica
- ▶ Buchholz (sudden pressure), ext. oil temperature, and aux. temperature protection via digital input
- ▶ Temperature measurement via external RTD-box (option)

SUPERVISION

- ▶ Current transformer supervision
- ▶ Circuit breaker failure protection
- ▶ Trip circuit supervision
- ▶ Cold load pickup
- ▶ Switch onto fault

RECORDERS

- ▶ Disturbance recorder: 120 s non volatile
- ▶ Fault recorder: 20 faults
- ▶ Event recorder: 300 events
- ▶ Trend recorder: 4000 non volatile entries

PC TOOLS

- ▶ Setting and analyzing software
Smart view for free
- ▶ Including page editor to design own Control pages
- ▶ SCADApter to re-assign datapoints for Retrofit projects: Modbus, Profibus, IEC 60870-5-103/ -104

CONTROL

- ▶ 2 breakers (or isolators / grounding switches)
- ▶ Breaker wear

COMMISSIONING SUPPORT

- ▶ USB connection
- ▶ Customizable Display (Single-Line)
- ▶ Customizable Inserts
- ▶ Copy and compare parameter sets
- ▶ Configuration files are convertible
- ▶ Forcing and disarming of output relays
- ▶ Fault simulator: current, voltage
- ▶ Graphical display of tripping characteristics
- ▶ 8 languages selectable within the relay

COMMUNICATION OPTIONS

- ▶ IEC 61850
- ▶ Profibus DP
- ▶ Modbus RTU and/or Modbus TCP
- ▶ IEC 60870-5-103
- ▶ IEC 60870-5-104
- ▶ DNP 3.0 (RTU, TCP, UDP)
- ▶ SCADApter

CYBER SECURITY

- ▶ Menu for the activation of security settings (e. g. hardening of interfaces)
- ▶ Security Logger
- ▶ Centralized Security Logs (Syslog)
- ▶ Encrypted Connection Smart view - Device
- ▶ Device specific certificates (No man in the middle attacks)

TIME SYNCHRONISATION

- ▶ SNTP, IRIG-B00X, Modbus, DNP 3.0, IEC 60870-5-103/-104

FUNCTIONAL OVERVIEW

	Elements	ANSI
Protective Functions		
Transformer differential protection (2 windings), Id:	1	87T
Curve with zero point and three settable slopes and highset element (Id>>), Inrush stabilisation / detection of 2nd, 4th and 5th harmonics		
Restricted earth fault IdG, IdG>>, characteristics similar to 87T	2	87TN
I, time overcurrent and short circuit protection (non-directional)	4	50P, 51P
Multiple reset options (instantaneous, definite time, reset characteristics according to IEC and ANSI)		
I2>, unbalanced load protection with evaluation of the negative phase sequence currents	2	46
ThR, overload protection with thermal replica for transformers IEC60255-8, alarm and trip threshold	1	49T
IH2/In, inrush detection with evaluation of the 2nd harmonic	2	Inrush
IG, earth overcurrent and short circuit protection (non-directional)	4	50N/G, 51N/G
Tremendous reset options (instantaneous, definite time, reset characteristics according to IEC and ANSI)		
ExP, External alarm and trip functions	4	
RTD temperature supervision via optional RTD-Box with 12 sensors		26
Control and Logic		
Control: Position indication, supervision time management and interlockings for 2 breakers		
Logic: Up to 80 logic equations, each with 4 inputs, selectable logical gates, timers and memory function		
Supervision Functions		
CBF, circuit breaker failure protection for both circuit breakers	2	50BF
TCS, trip circuit supervision	2	74TC
CTS, current transformer supervision	2	60L
CLPU, cold load pickup	1	
SOTF, switch onto fault	1	
BW, breaker wear	2	
Non volatile event recorder up to 120 s with 32 samples per cycles		
THD supervision		

APPROVALS / STANDARDS



certified regarding UL508 (Industrial Controls)



certified regarding CSA-C22.2 No. 14 (Industrial Controls)



certified by EAC (Eurasian Conformity)



Type tested and certified by KEMA Laboratories in accordance with the complete type test requirements of IEC 60255-1:2009.




KESCO 통일성 선언서

(Declaration of Identity)




Complies with "Engineering Recommendation G99 Issue 1 Amendment 6 - March 2020".
Complies with IEEE 1547-2003.
Amended by IEEE 1547a-2014.
Complies with ANSI C37.90-2005.

CONNECTIONS (EXAMPLE)



FUNCTIONAL OVERVIEW IN ANSI / IEEE C37.2 FORM

Typical Configuration



● Option

● Standard

● RTD (ANSI 26/38/49): requires URTD box (separate hardware)

ORDER FORM MRDT4

Non-directional Transformer Differential Protection				MRDT4	-2				
Version 2 with USB, enhanced communication and user options									
Digital Inputs	Binary output relays	Housing	Large display						
8	7	B2	-					A	
16	13	B2	-					D	
Hardware variants									
Phase Current 5 A/1 A, W1/W2 Ground Current 5 A/1 A									0
Phase Current 5 A/1 A, W1 Sen. Gr. Curr. 5 A/1 A, W2 Gr. Curr. 5 A/1 A									1
Phase Current 5 A/1 A, W1 Gr. Curr. 5 A/1 A, W2 Sen. Gr. Curr. 5 A/1 A									2
Phase Current 5 A/1 A, W1/W2 Sen. Gr. Curr. 5 A/1 A									3
Housing and mounting									
Housing suitable for door mounting									A
Housing suitable for 19" rack mounting **									B
Communication protocol									
Without protocol									A
Modbus RTU, IEC60870-5-103, DNP3.0 RTU <i>RS485/terminals</i>									B*
Modbus TCP, DNP3.0 TCP/UDP, IEC 60870-5-104 <i>Ethernet 100 MB/RJ45</i>									C*
Profibus-DP <i>optic fiber/ST-connector</i>									D*
Profibus-DP <i>RS485/D-SUB</i>									E*
Modbus RTU, IEC60870-5-103, DNP3.0 RTU <i>optic fiber/ST-connector</i>									F*
Modbus RTU, IEC60870-5-103, DNP3.0 RTU <i>RS485/D-SUB</i>									G*
IEC61850, Modbus TCP, DNP3.0 TCP/UDP, IEC 60870-5-104 <i>Ethernet 100MB/RJ45</i>									H*
IEC60870-5-103, Modbus RTU, DNP3.0 RTU <i>RS485/terminals</i>									I*
Modbus TCP, DNP3.0 TCP/UDP, IEC60870-5-104 <i>Ethernet 100 MB/RJ45</i>									J*
IEC61850, Modbus TCP, DNP3.0 TCP/UDP, IEC 60870-5-104 <i>Optical Ethernet 100MB/LC duplex connector</i>									K*
Modbus TCP, DNP3.0 TCP/UDP, IEC 60870-5-104 <i>Optical Ethernet 100MB/LC duplex connector</i>									L*
IEC60870-5-103, Modbus RTU, DNP3.0 RTU <i>RS485/terminals</i>									M*
IEC61850, Modbus TCP, DNP3.0 TCP/UDP, IEC60870-5-104 <i>Ethernet 100 MB/RJ45</i>									T*
Harsh Environment Option									
None									A
Conformal Coating									B
Available menu languages (in every device)									
English / German / Spanish / Russian / Polish / Portuguese / French / Romanian									

* Within every communication option only one communication protocol is usable. Smart view can be used in parallel via the Ethernet interface (RJ45).

The parameterizing- and disturbance analyzing software Smart view is included in the delivery of HighPROTEC devices.

Current inputs	4 (1 A and 5 A) with automatic CT Disconnect
Digital Inputs	Switching thresholds adjustable via software
Power supply	Wide range power supply
	24 V _{DC} - 270 V _{DC} / 48 V _{AC} - 230 V _{AC} (-20/+10%)
Terminals	All terminals plug type
Type of enclosure	IP54
Dimensions of housing (W x H x D)	19" flush mounting: 212.7 mm x 173 mm x 208 mm 8.374 in. x 6.811 in. x 8.189 in.
	Door mounting: 212.7 mm x 183 mm x 208 mm 8.374 in. x 7.205 in. x 8.189 in.
Weight (max. components)	approx. 4 kg

