



## Wireless multi-function handle RF TGM

### Features/Options:

- Metal enclosure
- sWave® wireless technology (SW868/SW915)
- Up to 4 push-buttons possible
- Collars (blue, red, green, black, grey) are included in delivery
- No wiring and pipe laying required
- Power supply by Lithium battery
- Easy programming of receiver
- Output signal can be individually configured at the receiver

### Technical data

Applied standards	EN 60947-5-1, EN 61000-6-2, EN 61000-6-3, EN 61000-4-2, EN 301 489-1, EN 301 489-3, EN 300 220-1, EN 300 220-2
Enclosure	stainless steel 1.4301
Degree of protection	IP 67 to IEC/EN 60529
Voltage supply	lithium battery Tadiran SL-361/P, 2/3 AA (battery incl. battery enclosure replaceable)
System	Li/SOC <sub>2</sub>
Nominal voltage	3.6 V
Nominal capacity	1.6 Ah
Battery life	> 800 000 operations
Switching system	push-button
Ambient temperature	-20 °C ... +65 °C
Switching frequency	max. 5 Hz
Wireless range	max. 450 m outside, max. 40 m inside
Mechanical life	> 1 million operations
Actuating time	min. 80 ms
Note	Transmission of battery voltage and switching condition
Wireless approvals	Europe: RED 2014/53/EU USA: FCC Part 15.247: XK5-RF Rx SW915 Canada: IC RSS-210: 5158A-RF Rx SW 915 Mexico: IFT - RCPSTRF17-1886