

## Pica II – High reliability in second generation.



### Highlights

- > Stable metal housing for industrial applications
- > Small footprint for applications with limited space
- > Serial, parallel and USB port
- > Display for comfortable operation
- > Cover with viewing window

### Options

- > LAN and WLAN 802.11 b/g interface
- > Guillotine cutter unit
- > Dispenser unit
- > Dispenser I/O
- > External label rewinder

### Guillotine cutter unit



### Dispenser unit



### External label rewinder



	Pica II 104/8	Pica II 106/12	Pica II 103/8 T	Pica II 108/12 T
<b>Printing</b>				
Print resolution	200 dpi	300 dpi	203 dpi	300 dpi
Print speed	max 100 mm/s	max 100 mm/s	max 100 mm/s	max 100 mm/s
Print width	max 104 mm	max 105.7 mm	max 104 mm	max 108.4 mm
Passage width	max 110 mm	max 110 mm	max 110 mm	max 110 mm
Printhead	Flat Type <sup>2</sup>	Flat Type <sup>2</sup>	Flat Type <sup>1</sup>	Flat Type <sup>1</sup>
<b>Labels</b>				
Adhesive labels, continuous labels	rolls or fan-fold: paper, cardboard, textile, synthetics			
Material weight	max 220 g/m <sup>2</sup> (larger on demand)			
Label width	min 15 mm			
Label height Standard Cutter mode/dispenser mode	min 6 mm min 15 mm			
Label height Standard Ethernet (option)	max 750 mm max 650 mm	max 750 mm max 650 mm	max 650 mm max 450 mm	max 650 mm max 450 mm
Roll diameter internal unwinder internal rewinder	max 180 mm -			
Core diameter	40 mm / 75 mm (option)			
Winding	outside or inside			
Label sensor Standard Option	transmission top transmission and reflexion / bottom transmission and reflexion			
<b>Transfer Ribbons (for thermal transfer printer only)</b>				
Ink	outside / inside (option)			
Core diameter	25.4 mm / 1"			
Roll diameter	max Ø 70 mm			
Length	max 300 m			
Width	max 110 mm			
<b>Fonts</b>				
Font types	6 bitmap fonts   8 vector fonts/TrueType fonts   6 proportional fonts   more fonts on demand			
<b>Bar Codes</b>				
1D bar codes	CODABAR, Code 128, Code 2/5 interleaved, Code 39, Code 39 extended, Code 93, EAN 13, EAN 8, EAN ADD ON, GS1-128, Identcode, ITF 14, Leitcode, Pharmacode, PZN 7 Code, PZN 8 Code, UPC-A, UPC-E			
2D bar codes	Aztec Code, CODABLOCK F, DataMatrix, GS1 DataMatrix, MAXICODE, PDF 417, QR Code			
GS1 bar codes	GS1 DataBar Expanded, GS1 DataBar Limited, GS1 DataBar Omnidirectional, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Truncated			
<b>Dimensions</b>				
width x height x depth	230 x 230 x 350 mm			
<b>Weight</b>				
Weight	9 kg			
<b>Interfaces</b>				
Serial	RS-232C (max 115,200 baud)			
Parallel	Centronics (SPP)			
USB	2.0 High Speed Slave			
Ethernet (option)	10/100 Base T, LPD, RawIP-Printing, DHCP, HTTP, FTP			
WLAN (option)	module 802.11 b/g/n WEP, WPA, WPA-PSK, WPA2, WPA2-PSK, EAP			
<b>Operating Conditions</b>				
Nominal voltage	230 V AC / 50 ... 60 Hz – 2 A   115 V AC / 50 – 60 Hz – 3 A (option) voltage adjustment by an internal voltage selector pre-adjustment 230 V AC			
Power	max 150 VA			
Operating temperature	5 ... 35 °C			
Relative humidity	max 80 % (non-condensing)			

<sup>1</sup> = Flat Type for thermal direct . <sup>2</sup> = Flat Type for thermal transfer