



"a preferred name in load cell technology"

Model 5530610





Shear Beam Load Cell

FEATURES:

- 1K to 40K pounds capacities
- Stainless steel construction
- Hermetically sealed
- Exceed NIST H-44 requirements
- Low cost
- Interchangeable with SSB
- Factory Mutual (F.M.) Approved †

APPROVED

DESCRIPTION:

Model SS30610 constructed of stainless steel, and hermetically sealed. The SS30610 load cell is an excellent choice for the toughest industrial environment. SS30610 is ideal for material processing, food processing and platform scales. Other capacities are available upon request.

PERFORMANCE SPECIFICATIONS									
Standard Capacities (lbs.):	1K, 2K, 4K, 5K, 10K, 40K								
Excitation Voltage:	15VDC								
Rated Output:	$2.0 \text{ mv/v} \pm .1\% \text{ mv/v}$								
Non-Linearity:	< 0.03% FSO (Full Scale Output)								
Hysteresis:	< 0.03% FSO								
Non-Repeatability:	< 0.02% FS0								
Zero Balance:	±1.0% FS0								
Bridge Resistance:	350 ± 1 ohms								
Safe Overload:	150% of Rated Capacity								
Temperature:									
Compensated Range:	0 - 150 deg. F								
Effect on Output:	< 0.0008% FSO/deg. F								
Effect on Zero:	< 0.0011% FSO/deg. F								
Material:	Stainless Steel								

Model 5530610



CAPACITY LBS.	Α	В	С	D	E	F	G	Н	- 1	J	K
1K - 5K	8.00	1.44	1.88	.51	.75	2.50	3.87	.68	1.18	.47	4.00
10K	9.25	1.88	2.75	.88	.80	2.63	4.88	1.00	1.63	.62	4.62
40K	12.50	2.75	3.75	1.31	1.25	3.50	6.25	1.50	1.88	.75	6.50


ELECTRICAL TERMINATION


INPUT OUTPUT SHIELD


GREEN (+) WHITE (+)

BLACK (-) RED (-)


COMPRESSION POSITIVE








† Factory Mutual Systems approved as intrinsically safe when installed per F.M. approved installation drawing. Contact ARTECH sales department for details.





1966 Keats Drive, Riverside, CA 92501

ORDER INFORMATION

- ARTECH is dedicated to maintaining adequate inventories of its Load Cells to provide the best service in the industry.
- Order by the model number and indicate the capacity required.
- Custom services such as matched load cell outputs, special threading, and custom calibrations are available on an optional basis at an extra cost.

Let us know what you need... we listen! QUALITY • PERFORMANCE • SERVICE

(951) 276-3331 (800) 654-8181 Fax: (951) 276-4556 Email: info@artechindustriesinc.com www.artechindustriesinc.com