

## PS12 USB

Desktop system  
with dynamic  
microphone and  
USB connection

Article-No.:  
**6401-003-000-40**



### Product:

#### Characteristics

- Dynamic unidirectional high noise canceling gooseneck microphone
- Device recognized as external sound card by the computer
- Buttons and LEDs recognized as HID (Human Interface Device)
- Compatible with Microsoft® Windows® XP, Vista and Windows® 7
- Demo software available

#### Options

- Electret microphone mounted on 8 mm gooseneck
- Various gooseneck lengths
- Special button colors or symbols
- Black matte housing

#### Application Range

- PC-based control centers in fixed indoor applications

#### Accessories

- WS16 windscreen
- Software sample kit (SSK)

#### Scope of Delivery

- Desktop system with USB cable
- Users manual

### Technical Data:

#### General

Microphone head:	Brass, sand blasted chrome (matte)	
Gooseneck:	Metal, matte silver coated	
Housing:	Metal, matte silver coated	
Dimensions:	Mic. head:	Length 80 mm, Ø 24 mm
	Gooseneck:	Length 200 mm, Ø 11 mm
	Housing:	Height 32 mm, Width 105 mm, Depth 160 mm
Weight:	770 g (27.1 oz)	
Connection:	2 m cable with USB-A plug	
Operating and display elements:	1 Button, black	
	1 LED, blue	
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)	
Operation temperature:	-10 °C to +55 °C (-14 °F to +131 °F)	

#### Microphone

Frequency range:	150 Hz to 12 kHz at -10 dB
Directivity:	Cardioid (at 1 kHz; 180° -20 dB)