

TM110

Dynamic hand
microphone
with one button

Article-No.:
2109-002-000-02



Product:

Characteristics

- Dynamic microphone capsule
- Unidirectional noise canceling
- Rugged chromed housing
- Durable PEIGUM® spiral cable
- Very long life switching contact

Options

- Protection against unintentional button presses
- Level control
- Push-button switch
- Customized plugs and cables
- Special button colors or symbols
- Black matte housing

Application range

- Radio systems in mobile and fixed applications

Accessories

- HV5 mount
- Rubber protective ring for microphone head
- Microphone preamplifier V966, V967, V856 and V857

Scope of delivery

- Hand microphone with PEIGUM® spiral cable

Technical Data:

General

Housing:	Brass, brushed chrome
Dimensions:	Length 142 mm, Head Ø 29 mm, Body Ø 24 mm
Weight:	210 g (7.4 oz)
Connection:	4-wire halogen free PEIGUM® spiral cable, 2 Wires shielded, Draw length max. 1.5 m, without connector
Operating and display elements:	1 Button, black
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-20 °C to +60 °C (-4 °F to +140 °F)

Microphone

Frequency range:	300 Hz to 6 kHz at -10 dB
Sensitivity:	2 mV/Pa (-54 dBV/Pa ± 3 dB)
Impedance:	200 Ω ± 20 % at 1 kHz
Directivity:	Cardioid (at 1 kHz; 180° -15 dB)