

# SE-0010 ESENSE CO2 MONITOR FOR LEED SE-0010



## Low Cost and Maintenance Free

The **eSense LEED Fresh Air Indicator (FAI)** is a simple, low-cost and maintenance-free carbon dioxide monitor designed to be installed in areas like **office buildings** or **classrooms** where the carbon dioxide levels need to be monitored for indoor air quality. An audible and visual signal indicate when recommended indoor carbon dioxide levels are exceeded.

## Features

- Three colored LEDs
  - Red
  - Yellow
  - Green
- Meets LEED 2.2 standards
- Audible alarm and Mute button
- Mounts on US-Standard J box
- Automatic self-diagnostics
- Maintenance-free

## Applications

- Homes
- Offices
- Commercial Buildings
- Classrooms
- Fitness Studios

## Accessories

CM-0106 - 24V Power Supply (works with eSense FAI).

Our 24VDC replacement power supply is used to power many of our low voltage, non-grounded devices. This power supply features a full complement of adapters that allows them to be used in the US and worldwide..



# SE-0010

## ESENSE CO2 MONITOR FOR LEED SE-0010

### General Specifications

#### Specifications

General Performance Compliance with EMC directive 89/336/EEC,

RoHS directive 2002/95/EG

Meets ISO 12039 Standard for NDIR detection of CO2

Protection Class IP30

Sensor Life Expectancy: 15 years


### Electrical and Mechanical Specifications

#### Power Supply

Power Input: 12-30 VAC/VDC, 50/60HZ

Power Supply: 120/ 240 VAC 50/60 Hz to 24VAC Adapter

Power Consumption: < 1 Watt average



Call 1.877.678.4259

Email [Sales@CO2Meter.com](mailto:Sales@CO2Meter.com) | [Support@CO2Meter.com](mailto:Support@CO2Meter.com)

Web [CO2Meter.com](http://CO2Meter.com)

Let's Get Social – @CO2Meter on:



Last Update: 4-16-2021