

## Mechanical Time Switch - 24-Hour Heavy-Duty Metal Dial Mechanical Time Switch with Skip-a-Day, 480 VAC, 60Hz, SPDT, Indoor Metal Enclosure, 15 Minute Interval

Item T1975EHD



### PRODUCT DESCRIPTION

These heavy-duty time switches are designed to handle the toughest environments and have fully encapsulated motors to prevent dust or debris from entering the motor. The ON/OFF trippers are permanently attached to the metal dial to avoid the accidental loss of a tripper. These time switches offer 15-minute intervals, providing up to 96 operations each day.

### FEATURES

- ▶ Heavy-duty metal dial and metal enclosure withstands the most punishing environmental conditions
- ▶ Models with skipper wheel allow for operations to be omitted on selected days of the week
- ▶ Easy-to-set trippers rotate in/out for fast, accurate setting
- ▶ Up to 96 operations (48 ON/48 OFF) every 24 hours
- ▶ 15-minute intervals between events
- ▶ Fully encapsulated motor with protected gears

### APPLICATIONS

- ▶ Timing/Scheduling ON/OFF
- ▶ Indoor Lighting Control

### TECHNICAL DATA

#### General

Model Number	T1975EHD
Description	24-Hour Heavy-Duty Metal Dial Mechanical Time Switch with Skip-a-Day, 480 VAC, 60Hz, SPDT, Indoor Metal Enclosure, 15 Minute Interval
UPC Code	078275127722
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Control Specifications

Minimum ON/OFF Times	15 min
Maximum ON/OFF Operations	48
Skipper Wheel	24 Hour
Operation Mode	24 hour
Has Manual Override	Yes

#### Mechanical Specifications

Enclosure Type	Indoor type 1 metal
Number of Trippers Included	96

#### Dimensions

Product Dimensions (H x W x D) in	7.875 x 5.125 x 3.4375 in
Wire Size Min	#14 AWG
Wire Size Max	#12 AWG

#### Load Ratings

Motor	1/2 HP, 125 VAC, 60 Hz;1 HP, 250 VAC, 60 Hz
Resistive Load Ratings Ranges	20 A, 125-480 VAC, 60 Hz

### Electrical Specifications

Wiring Option	Terminals
Input Voltage Range(s)	480 VAC, 60 Hz
Number of Circuits	1
Switch Type	SPDT
Maximum Power Consumption (W)	3 W

### Packaging

Shipping Weight (lbs)	3.064
Unit Carton Dimensions (H x W x L) in	8.25 x 3.5 x 5.5 in

### Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

### Standards and Certifications

CSA Certification	cCSAus
California Proposition 65	Lead


**ACCESSORIES**



156T1950A  
Set of 12 Trippers for T1900, T2000, C8800, R8800 and T8800 Series

**Product Image Not Available**

156T1950AD12  
12 Bags of 156T1950A Trippers for T1900, T2000, C8800, R8800, and T8800 Series



22T338GR  
Mounting Bracket for Intermatic Standardized Timer Mechanisms

**Product Image Not Available**

124T905  
Insulator for T1905HDM, T1975EHDM, T1975HD, T1976, T1975, T1975ER, T1905



WG730-14D  
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG730-14DMX  
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG733-14D  
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG733-14DMX  
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series

**Product Image Not Available**

156T1957A  
Skipper Screws (3 per package)

**Product Image Not Available**

156T2978A  
Package Accessory Trippers