


OUTLET FLANGE DETAIL



TECHNICAL SPECIFICATIONS

DIMENSIONS

| Model | Cutting width | Minimum working length | Maximum working length | Suction channels | Weight (standard version) | Pneumatic feeding (ISO Class 2.4.1 according to 8573-1: 2010) | Max pressure level of compressed air | Compressed air consumption | Max cutting thickness | Admissible max load | Total width of cutting table | C-C distance of suction channels | Width of cutting table | Width of the ditch |
|---------|---------------|------------------------|------------------------|------------------|---------------------------|---------------------------------------------------------------|--------------------------------------|----------------------------|-----------------------|---------------------|------------------------------|----------------------------------|------------------------|--------------------|
| | [mm] | [mm] | [mm] | | nr | | | | | | kg/m | [mm] | bar | Nl/activation |
| HT-2000 | 2000 | 3000 | 60000 | 2 | 1220 | 2xØ8 | 8 | 1.2 | 500 | 4000 | 3095 | 2700 | 2445 | 2060 |
| HT-2500 | 2500 | | | | 3595 | | | | | | 3200 | 2945 | 2560 | |
| HT-3000 | 3000 | | | | 4095 | | | | | | 3700 | 3445 | 3060 | |
| HT-3500 | 3500 | | | | 4595 | | | | | | 4200 | 3945 | 3560 | |

Suction area 750 mm STANDARD - Suction area 500 mm OPTIONAL