

1535

Air Carry-On Case

Peli[™] Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 40 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Peli[™] Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

• Maximum airline carry on size*

 \bullet Automatic Pressure Equalization Valve - balances interior pressure, keeps water out

Automatic Pressure Equalization Valve - balances interior pressure, keeps water out

- Fold down overmolded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- Quiet Rolling Stainless-Steel Bearing Wheels
- *Check with your airline for exact measurement requirements
- Press and Pull[™] Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX²[™] Polymer up to 40% lighter
- Waterproof O-ring seal
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



CONFIGURATIONS



1535 Standard



1535NF

No Foam





1535TP led Dividers With TrekPak Divider System





1535WF With Foam



1535AIRTPF TrekPak / Foam Hybrid

DIMENSIONS

Interior (L×W×D)	20.39 x 11.20" x 7.21 (51.8 x 28.4 x 18.3 cm)
Exterior (L×W×D)	21.96 x 13.97" x 8.98 (55.8 x 35.5 x 22.8 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	5.21" (13.2 cm)
Total Depth	7.21" (18.3 cm)
Int Volume	0.95 ft³ (0.027 m³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Proprietary Polypropylene Blend		
Latch	ABS		
O-Ring	EPDM		
Purge Body	ABS		
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven		

COLOURS

Black	Orange	Silver	Yellow	
Graphite				

WEIGHT

leight With Foam	9.98 lbs (4.5 kg)
leight Empty	8.69 lbs (3.9 kg)
uoyancy	64.80 lbs (29.4 kg)
/eight With TrekPak / oam Hybrid	11.91 lbs (5.4 kg)

TEMPERATURE

Minimum Temperature	-60°F (-51.1 °C)
Maximum Temperature	160°F (71.1 °C)

2

OTHER

Wheels

ACCESSORIES



Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 08-04-22