



IS Series

Mid-Frequency Inverter Resistance Welding Control

- 300, 800, and, 1400 Amp primary output current **resistance weld control**
- Six feedback modes for optimum feedback based on process and expected variability
- Built-in current, voltage, power, time and pulse monitor for precise process control
- Triple pulse weld profile: W1, W2, W3, up to 19 pulsations per weld segment
- Displacement and force monitoring Initial, Final and "Weld to" displacement
- Cascade option: 5 and 7 way cascade IS-800CA only
- RS232, RS485, EtherNet/IP communications

KEY FEATURES

Wide Current Range

The IS Series weld controls provide a wide range of current (.050 kA - 80 kA) to meet all your application needs. See specifications of individual controls on back. Higher current up to 320 kA available upon request.

Displacement Limits & Force Monitoring

Dial-in the weld process by utilizing the IS Series' displacement and force features including initial part thickness, weld-displacement, and final displacement limits. Monitor the force of each segment of the weld pulse.

Six Weld Control Modes

Six different weld control modes allow the user to select the best mode for the application: primary limit, primary and secondary RMS, power RMS, voltage control, or pulse percent.

Triple Pulse Weld Capability

Provides flexible weld profiles with up to three pulses in each weld cycle. Each weld segment can be programmed with upslope and downslope and may have up to 19 pulsations per segment. Users may change the control mode for each weld segment.

Factory Automation with Ethernet IP

Ethernet IP factory communications comes optional IS Series for integration into automation environments. It comes with built in Panel View screens for easy control of IS unit.


TYPICAL APPLICATIONS




Commutator fusing



Wire termination



Sheet metal welding



Braided cable termination

TECHNICAL SPECIFICATIONS

	IS-300CA	IS-800CA	IS-1400CA	IS-2200CA*
Maximum primary output current*	300 amps @ 4.4%	800 amps @ 3%	1400 amps @ 3%	2200 amps @ 12%
Settings				
– Constant current	0.05 - 20.00 kA	0.05 - 40.0 kA	0.05 - 80.0 kA	2.00 - 160 kA
– Constant power	0.05 - 20.0 kW	0.05 - 60.0 kW	0.05 - 120 kW	2.00 - 240 kW
– Constant voltage	0.20 - 9.99 V	0.20 - 9.99 V	0.20 - 9.99 V	0.20 - 9.99 V
– Fixed pulse	10.0 - 99.9%	10.0 - 99.9%	10.0 - 99.9%	10.0 - 99.9%
Weld monitors				
– Current	0.0 - 99.9 kA	0.0 - 99.9 kA	0.0 - 99.9 kA	0.0 - 999.9 kA
– Power	000.0 - 999.9 kW	000.0 - 999.9 kW	000.0 - 999.9 kW	000.0 - 999.9 kW
– Voltage	0.00 - 9.99 V	0.00 - 9.99 V	0.00 - 9.99 V	0.00 - 9.99 V
– Pulse %	10.0 - 100%	10.0 - 100.0%	10.0 - 100.0%	10.0 - 100.0%
Power source	380 - 480 VAC, Three Phase, 50/60 Hz, ±10%			
Output frequency**	600 - 3000 Hz	600 - 3000 Hz	600-3000 Hz	600-3000 Hz
Control modes	Primary constant current control Primary limit control Secondary RMS control Power RMS control Voltage control Pulse % control			
Number of schedules	255 (Selectable by pendant or external I/O)			
Time settings	0000 - 9999 (ms) / 0000 - 9999 (CYC)			
Squeeze delay	0000 - 9999 (ms) / 0000 - 9999 (CYC)			
Squeeze	000 - 999 (ms) / 00 - 50 (CYC)			
Upslope 1, 2, 3	000 - 999 (ms) / 00 - 50 (CYC)			
Weld 1, 2, 3	0000 - 9999 (ms) / 0000 - 0999 (CYC)			
Cool 1, 2	000 - 999 (ms) / 00 - 50 (CYC)			
Down slope 1, 2, 3	00000 - 20000 (ms) / 00000 - 00999 (CYC)			
Hold	0 or 0010 - 9990 (ms) / 0000 - 0099 (CYC)			
Off time	01 - 19 (settable for WELD 1 to WELD 3, respectively)			
Pulsation setting				
Transformer turns ratio	1.0 - 199.9			
Valve setting	Up to 6 valves	Up to 6 valves	Up to 6 valves	Up to 6 valves
Control gain (GAIN)	1 - 9			
Step-up/-down (STEPPER COUNT)	STEP Up (down) ratio (RATIO) Counter setting (COUNT)		1 - 9 (9 steps) 50 - 200% 0000 - 9999	
Weld count monitor (PRESET COUNT)	0000 - 9999			
External communication	RS-232 or RS-485 (single or bidirectional), EtherNet/IP			
Program protect	Programming protected when active			

*2200 A, 2-160 kA secondary and 4500 A primary, 32-320 kA secondary settable range - available upon request.

Contact factory for more details on the 4500 A model.

**Model dependent

WEIGHT & DIMENSIONS

	IS-300CA	IS-800CA	IS-1400CA	IS-2200CA
Dimensions	11 in x 7 in x 23 in	13 in x 30 in x 39 in	13 in x 31 in x 52 in	15 in x 31 in x 55 in
L x W x H	(269 mm x 172 mm x 573 mm)	(330 mm x 772 mm x 991 mm)	(330 mm x 796 mm x 1321 mm)	380 mm x 787 mm x 1396 mm
Weight	36 lb (16.5 kg)	240 lb (109 kg)	350 lb (159 kg)	320 lb (145 kg)

Options & accessories	EtherNet/IP, RS-485 communications (RS-232 standard) CE Filter Isolation contactors Programming pendant MA-660A	24 VDC valve option(115 VAC standard) • 2 amp • 5 amp 250 VA valve transformer (150 VA standard)
----------------------------------	--	---



AMADA WELD TECH INC.

1820 S. Myrtle Ave. • Monrovia, CA 91016 US
T: (626) 303-5676
info@amadaweldtech.com • www.amadaweldtech.com
ISO 9001 Certified Company • 24/7 Repair Service: 1-866-751-7378

AMERICAS

AMADA WELD TECH
(Midwest Technical Center)
Detroit, Michigan
T: (248) 313-3078
midwestsales@amadaweldtech.com

AMADA WELD TECH DO
LTDA.
São Paulo, Brasil
T: +55-11-4193-3607
antonio.ruiz@amadaweldtech.com

EUROPE

AMADA WELD TECH
GmbH
Munich, Germany
T: +49-89-839403-0
infode@amadaweldtech.eu

ASIA

AMADA WELD
TECH CO., LTD.
Isehara, Japan
T: +81-4-7125-6177
sales@miyachi.com

AMADA WELD TECH
KOREA CO., LTD.
Seoul, Korea
T: +82-31-8015-6810
sales@amadaweldtech.co.kr

AMADA
(THAILAND) CO., LTD.
Bangkok, Thailand
T: +66-2170-5900
info@amada.co.th

AMADA WELD TECH
INDIA PVT., LTD.
Bangalore, India
T: +91-80-4092-1749
info@miyachiindia.com

AMADA WELD TECH
(Mexico Office)
El Paso, Texas
T: (915) 881-8765
mxsales@amadaweldtech.com

AMADA WELD TECH
SHANGHAI CO., LTD.
Shanghai, China
T: +86-21-6448-6000
jwu@msc.miyachi.com

AMADA WELD TECH
TAIWAN CO., LTD.
Taipei, Taiwan
T: +886-2-2585-0161

AMADA
VIETNAM CO., LTD.
Ha Noi, Vietnam
T: +84-4-6261-4583

Specifications subject to change without notice. Copyright © 2020 AMADA WELD TECH INC. The material contained herein cannot be reproduced or used in any other way without the express written permission of AMADA WELD TECH INC. All rights reserved.

follow us on:



03/20