

POWER SENSORS

Precision Directional RF

4027A SERIES



Accuracy and Precision for Laboratory Applications

The 4027A Series Power Sensors from Bird bring superb accuracy and ease of use together for the laboratory engineer. In semiconductor processing and other precision process applications where accuracy is critical, these sensors are capable of 1% accuracy at the calibrated frequency and power level. Calibration is traceable to the National Institute of Standards and Technology (NIST), providing additional confidence in sensor measurement.

PRODUCT FEATURES

- 1% accuracy at specified frequencies and power levels minimizing poor production yields
- Models do not need to be field calibrated before use and only need to be calibrated once every six months
- Plug and Play with the 4421A Multifunction Meter
- Dozens of connector options available
- Calibration traceable to the National Institute of Standards and Technology

FOR USE WITH

- 4421A Multifunction Power Meters
- SCC7 Calibration Cart
- MSCC7 Calibration Cart

PRECISION DIRECTIONAL RF POWER SENSORS

4027A SERIES

Specifications

MEASUREMENT

Accuracy	±1% at calibration frequencies and power levels ±2% at other frequency and power levels Add 2% to uncertainty outside 25 ± 10 °C
Uniformity	2% maximum unit to unit, at calibration frequency and power levels
Speed	2 readings per second
Harmonic Content	-50 dBc max
VSWR Range	1.00 to 2.00
Directivity	28 dB
Insertion Loss	<0.05 dB
Calibration Power Level	1000 W units: 700 watts Other units: 1700 watts
Maximum Power	Sensor Frequency Dependent

CONNECTORS

RF Connectors	Customer specified
----------------------	--------------------

SYSTEM

Recommended Calibration Interval	6 month. Performance before and performance after data supplied with recalibrations
Power Supply	External DC, 12 VDC, supplied from Bird 4421A Power Meter

PRODUCT SELECTION GUIDE

Model Number	Power Range	Frequency (MHz)
4027A12M	300 mW to 1 kW	10-15 MHz
4027A250K	3 W to 10 kW	250-400 kHz
4027A400K	3 W to 10 kW	400-550 kHz
4027A800K	3 W to 10 kW	800-950 kHz
4027A2M	3 W to 10 kW	1.5-2.5 MHz
4027A4M	3 W to 10 kW	3-5 MHz
4027A10M	3 W to 10 kW	10-15 MHz
4027A25M	3 W to 9 kW	25-30 MHz
4027A35M	3 W to 7.5 kW	35-45 MHz
4027A60M	3 W to 6 kW	45-65 MHz
4027A100M	3 W to 4 kW	95-105 MHz
4027A150M	3.75W to 3.75 kW	150-170 MHz

ENVIRONMENTAL

Operating Temperature	0 °C to 50 °C (32 °F to 122 °F)
Storage Temperature	-20 °C to 70 °C (-4 °F to 158 °F)
Humidity	95% max (non-condensing)
Altitude	Up to 10,000 ft (3,048m)

PHYSICAL

Size	5.2 in x 2.5 in x 3.25 in (137 mm x 64 mm x 83 mm)
Weight	1 lb 13 oz (0.8 kg)

CERTIFICATIONS

EMC	Designed to carry CE mark
------------	---------------------------

birdrf.com/products

The RF Experts | USA Sales : 30303 Aurora Rd, Solon, OH 44139 | www.birdrf.com
Phone: +1 440.248.1200 / 866.695.4569 [Toll Free] | Fax: +1 440.248.5426 / 866.546.4306 [Toll Free]

Bird is not responsible for omissions or errors. Specifications subject to change without notice.
©2020 Bird • Precision-Directional-RF-Power-Sensor-4027A-Series-09092020

