RPS-M-3131SC300BHA10LL024 (Order no. 119839)

Rope pull switch with pull-to-reset button for emergency stop device, clamping head, plug connector MR10


- Metal housing
- EMERGENCY STOP device with detent mechanism according toEN ISO 13850 and EN 60947-5-5
- Clamping head for pull wire
- Indication of correct rope tension
- Plug connector MR10
- LED left
- Switching elements with 4 switching contacts



Switching elements

3131 Slow-action switching contact 2 NC \rightarrow + 2 NO


Dimensional drawings



18,3


35,5

Connection examples





Shift travel diagrams



Actuating force ± 15%



Technical data

Approvals



Operating and display elements

LED display

LED display	
DC	24 V
	(left switches red LED)
Electrical connection values	
Rated insulation voltage U _i	50 V
Rated impulse withstand voltage U _{imp}	2.5 kV
Utilization category	
AC-15	3 A 50 V
DC-13	0.27 A 50 V
Short circuit protection according to IEC 60269-1	4A gG
Switching current	
at 24V	min. 10 mA
thermal rated current I _{th}	4 A
Mechanical values and environment	
Connection type	Plug connector MR10
connection type	(10-pin (without PE) – bottom)
Number of NO contacts	2
Number of positively driven contacts	2
Actuation frequency	max. 1200 1/h
Actuating force	300 N
Installation orientation	any
Mechanical life	0.1 x 10 ⁶

Slow-action switching contact

Switching principle

Degree of protection	IP65
Rope diameter	2 5 mm
Ambient temperature	−20 +50 °C

Material

Housing Die-cast aluminum

Characteristic values according to EN ISO 13849-1 and EN IEC 62061

	B10 _D	Mission time
Emergency stop	0.2x10 ⁶	20 y

Miscellaneous

Additional feature

Emergency stop function

Downloads

All documentation for this material can be found on our website: <u>https://www.euchner.de/en-us/a/119839/?#downloads-tab</u>

Ordering data

Ordernumber	119839
Item designation	RPS-M-3131SC300BHA10LL024
Gross weight	1,27kg
Customs tariff number	85365019000
ECLASS	27–37–12–01 Emergency stop pull cord switch



Accessories

Connection accessories

102516

Connecting cable with plug connector MR10, 10-pin, 1.8 m



C-MINF10-10X1,0PU01,8-MA-102516

- MR10 female plug, 10-pin
- Straight plug connector
- PUR cable
- Cable length 1.8 m
- With flying lead

Connecting cable with plug connector MR10, 10-pin, 12.1 m



102519 C-MINF10-10X1,0PU12,1-MA-102519

- ► MR10 female plug, 10-pin
- Straight plug connector
- PUR cable
- Cable length 12.1 m
- With flying lead

Connecting cable with plug connector MR10, 10-pin, 15.2 m



102520 C-MINF10-10X1,0PU15,2-MA-102520

- ► MR10 female plug, 10-pin
- Straight plug connector
- PUR cable
- Cable length 15.2 m
- With flying lead

Connecting cable with plug connector MR10, 10-pin, 18.2 m



102521 C-MINF10-10X1,0PU18,2-MA-102521

- ▶ MR10 female plug, 10-pin
- Straight plug connector
- PUR cable
- Cable length 18.2 m
- With flying lead

Connecting cable with plug connector MR10, 10-pin, 3.6 m



102517 C-MINF10-10X1,0PU03,6-MA-102517

- ▶ MR10 female plug, 10-pin
- Straight plug connector
- PUR cable
- Cable length 3.6 m
- With flying lead

Connecting cable with plug connector MR10, 10-pin, 6 m

	-	
		

102518 C-MINF10-10X1,0PU06,0-MA-102518

- MR10 female plug, 10-pin
- Straight plug connector
- PUR cable
- Cable length 6 m
- With flying lead

Connecting cable with plug connector MR10, 10-pin, 9.1 m



100956 C-MINF10-10X1,0PU09,1-MA-100956

- MR10 female plug, 10-pin
- Straight plug connector
- PUR cable
- Cable length 9.1 m
- With flying lead

Mounting accessories

Eyebolt for rope pull switches Eyebolt with thread M8 092495 RPS-0-8-50/V5 Pulley set RPS-P/V1 for rope pull switches Rope pulley block Ø 14 mm 096251 RPS-P-7-70 Pulley set RPS-PS/V5 for rope pull switches • Pulley set consisting of rope pulley block and 092501 pulley support RPS-PS/V5 Rope set for rope pull switches 092496 • Rope set consisting of thimble and rope clamp RPS-RS/V5 Tensioner spring for rope pull switches Tensioner spring for tensile force 300 N 092138 **RPS-W-300** Tensioning rope for rope pull switches 092814 Tensioning rope with 100m length RPS-I-3-4/100M • Tensioning rope with 50m length 092813 RPS-I-3-4/50M Turnbuckle for rope pull switches Turnbuckle M6 x 100 092500 RPS-B-6-110 092498 ▶ Turnbuckle M6 x 60 RPS-B-6-60/V5