

Product Datasheet

Pedestal mounted eye wash with GRP closed bowl

STD-25K/P

STD-25KS/P

For immediate relief of the eyes and/or face following a dangerous substance spillage or splash this pedestal mounted eye/face wash provides 12 litres per minute of water to flush the effected area. Manufactured from glass reinforced plastic (GRP) it is strong, durable and resistant to rust. For areas where low water pressure is an issue, modified diffusers can be fitted to ensure a perfect water flow is sustained. The integral handheld eye, face and body shower is ideal to wash specific areas of the body that may also have been affected. Designed in accordance with EN15154 and ANSI Z358.1-2014 standards.



Specifications

MATERIALS OF CONSTRUCTION	
BOWL/LID	GRP
DIFFUSERS	Chrome plated brass retaining ring, stainless steel filter mesh, plastic body
PIPEWORK	Stainless steel (GS) or galvanised mild steel (G)
STANDARD FINISH	Green powder coated (alternative colours available) (G) Polished brush finish (paint options available) (GS)
SERVICES	
WATER INLET	1 1/4" Male BSP
OPERATING PRESSURE	2.0 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	Eye wash: 12 L per minute / 3 US gal per minute Handheld: 8 L per minute / 2 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
EYE/FACE WASH	Lift lid (optional foot treadle control for hands free operation)
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	500mm (19.6in) x 537mm (21.1in) x 1106mm (43.5in)
WEIGHT	13kg / 29lb

General Arrangement Drawing

Pedestal mounted eye wash with GRP closed bowl

STD-25K/P

STD-25KS/P

