

MINI PROBE SET



7220.840.SET



7220.844.C



7220.841

- For the point to point measurement on small packaging and inside cavities
- Conductive rubber electrodes ($R < 20 \text{ ohm}$)
- Spring loaded mechanism for good contact
- Quick removable head
- Complies with IEC 61340-4-10
- Incl. calibration certificate



sample application

IEC
EN

Part Nr.

7220.840.SET	Miniprobe Set Model 840 incl. conductive carrying case and a 2 point probe tip/model 844
7220.844.1	Replacement pins for probe tip 844 (unit: 2 pcs)
7220.844.C	Calibration Unit for Two-Point-Probe, incl. calibration certificate
7220.841	Probe tip „mini ring probe“ (optional for 7220.840.SET), incl. calibration certificate

POINT-TO-POINT PROBE MODEL 860



- For the point to point and resistance to ground measurement at a 30 cm fixed distance between the electrodes
- Must be connected to a high resistance Ohmmeter
- Conductive rubber ($R < 5 \text{ ohm}$) with silver particles
- 950 g weight
- Dimensions: 385 x 85 x 70 mm (L x W x H)
- Contact rubber: $\varnothing 63,5 \text{ mm}$
- Incl. calibration certificate

Part Nr.

7220.860	Point-to-point probe model 860
-----------------	--------------------------------

METAL PLATE



7100.PGT100.102



2287.10.10



sample application

- Dimension: 400 x 300 x 2 mm
- 10 mm snap
- For measuring shoes, chairs, transportsystems etc.
- Connection with 10 mm snap / 4 mm banana plug adapter

Part Nr.

7100.PGT100.102	Metal plate
2287.10.10	Banana plug adapter