

UVX-300G-C

LUMINESCENCE SENSOR

Confirm manufacturing processes more reliably than vision systems that cost ten times more. The UVX™ employs our field-proven, patented technology, for effective detection of glues and adhesives in assembly, manufacturing and packaging processes. It can be used to check for gaps in glue dispensing operations, excess glue on joints and clogged nozzles. Even transparent glue is reliably detected. High-sensitivity and fast response makes the UVX suitable for high-speed automation processes. The metal alloy case and glass lens provide robust construction expected in an industrial environment.

The UVX features a 2-digit display that provides an indication of signal strength making set-up and integration quick and easy. The versatile sensor provides user set-up parameters including light source intensity adjustment, detection threshold and adjustable gain, making the UVX useful in a wide range of applications.

The UVX includes both a discrete PNP/NPN output and an analog output. The discrete output is automatically set for PNP or NPN operation. The analog output signal may be used to assess the relative quantity of UV materials such as optical brightener coatings applied to clear films.

UVX





Applications

- Adhesives, gums and glues
- Labels, packaging
- UV inks, visible and invisible
- UV crayons and chalk, lumber marking
- Tamper-evident-seals
- Textiles, luminescent threads
- Optical brightness, paper industry
- Grease and oils

Design & Features

- Small spot size
- High sensitivity and high resolution
- Fast response
- Display range 00-99
- Adjustable gain
- Analog output
- PNP/NPN discrete output
- FGC model for suppression of blue

Ordering Information



UVX-300 G-C
Luminescence sensor



UVX-300 G-FGC
Luminescence sensor
>500nm spectral response

Accessories



UVX-300L50
50 mm focal lens



UVX-300B
Bracket



UVX-300C
Cable 5P, 5M, M12, F

**NOT INTENDED FOR USE IN
PERSONAL SAFETY APPLICATIONS.**

Functions

NORMAL OPERATING MODE
CALIBRATION
THRESHOLD
UV LED INTENSITY
HYSTERESIS LEVEL
DISCRETE OUTPUT
OUTPUT PULSE STRETCH
SECURITY
TEACH MODE

Displays relative reflection intensity
User sensitivity adjustment
Set detection level
Set LED, LO, MED, HI
Set undetect level 1-9 steps below threshold
Set normally open or normally closed
Set minimum output period 10...90mS
Lock/unlock pushbutton controls
Auto-set detection threshold

Specifications

Light source
370nm UV LED, 100,000 hrs.
Light spot size
6...8mm dia. @ 50mm
Light source intensity
3 levels
Sensing distance
up to 350mm
Receiver Spectral Resonance (FGC model)
350...1000nm
Receiver Spectral Resonance (FGC model)
500...1000nm
Response time
<150uS
Switching Frequency
6kHz
Relative intensity display range
00 to 99
Sensitivity
Adjustable
Signal level
Two 7 segment digits
Detection threshold
Two 7 segment digits
Digital Output
Auto-Detect PNP / NPN
Output Function
NO/NC selectable
Analog Output
0...5V
Power indicator
Green LED
Detect indicator
Red LED
Programming indicator
Yellow LED
Data retention
EEPROM non-volatile memory
Dimensions
51mm x 61mm x 25mm
(2.0" x 2.4" x 1.0")
95 g (0.21 lbs.)
Weight
24 VDC
Supply Voltage
60 mA
Operating Current
Discrete output
Short Circuit Protection
Supply voltage
Overload / Reverse Polarity Protection
-20°C...55°C
Operating temperature
-20°C...70°C
Storage temperature
Metal alloy
Housing
IP65 NOT FOR PRESSURE WASHDOWN
Mechanical Protection


370nm UV LED,
100,000 hrs.
6...8mm dia. @ 50mm
3 levels
up to 350mm
350...1000nm
500...1000nm
<150uS
6kHz
00 to 99
Adjustable
Two 7 segment digits
Two 7 segment digits
Auto-Detect PNP / NPN
NO/NC selectable
0...5V
Green LED
Red LED
Yellow LED
EEPROM non-volatile memory
51mm x 61mm x 25mm
(2.0" x 2.4" x 1.0")
95 g (0.21 lbs.)
24 VDC
60 mA
Discrete output
Supply voltage
-20°C...55°C
-20°C...70°C
Metal alloy
IP65 NOT FOR PRESSURE WASHDOWN

Indicators

7-Segment display
LED
Green LED Power
Red LED Detect
Yellow LED Program

Connector M12

Pin 1 Power to 24VDC
Pin 2 Discrete output
PNP/NPN NO/NC
Pin 3 Ground
Pin 4 Analog output 0 to
5V DC
Pin 5 Remote LOCK/
UNLOCK input



WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of manufacture. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship.